



East Coast Office: 800-215-8563  
West Coast Office: 800-848-4444  
Rosito-Bisani.com

## **Espresso Machine Installation Requirements (Three Group Espresso Machine)**

### **Supplied by Customer**

#### **Plumbing**

- Cold Water Line
  - On/Off Shut-Off Valve with 3/8 inch compression fitting within 6 feet of espresso machine
  
- Open Floor Sink Drain within 4 feet of espresso machine

#### **Electric**

- Power
  - 220 Volts
  - 30 Amp Dedicated Circuit
- Wall Receptacle
  - Receptacle (Twist and Lock): NEMA L630R
  - Within 4 feet of espresso machine

\*(If there is an existing 220 volt wall receptacle....we will need the existing plug or NEMA number to match accordingly)

#### **Drilling**

-2 to 3 inch diameter hole ONLY on hard surfaces such as marble, granite, stainless steel, polished metal, tile, and other custom finishes.

### **Supplied by Rosito Bisani**

#### **Qualified Installation/Service Technician**

#### **Installation Materials**

- All necessary hoses, fittings, pipes to connect machine to shut-off valve
- Plug to match receptacle
- Installation of Water Softener (if purchased through Rosito Bisani)

#### **Drilling**

- Wood surfaces

**Please feel free to have your plumber or electrician contact us with any questions, concerns, or comments, regarding the installation requirements.**

# SAMPLE SET UP

## 208/230 Voltage Application

